

Epson LX-1350

DATASHEET



With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

This wide-carriage 9-pin printer fits perfectly into a range of environments including data reporting, listings and point-of-sale. It is 337 cps fast, very reliable and cost efficient and has a range of options so you can create the perfect high quality printer to match your changing business requirements.

Flexible working

Handle light duties in style with printing up to A3 size, 5-part forms (1 original + 4 copies) and 337 cps (12dpi) speed.

Get connected

Enjoy no-fuss support for a range of office equipment with auto switching between USB, parallel and serial sources.

Optional extras

Choose from a wide range of options to match changing needs, including a 50 cut-sheet feeder, and roll paper holder.

KEY FEATURES

- Wider format
Fast, reliable 9-pin printing up to A3
- High productivity
Print up to 337 characters per second (12 dpi)
- Multi-part flexibility
Print up to 5-part forms (1 original 4 copies)
- Paper handling
Top, bottom, front and rear paper paths
- Easy connectivity
Auto switch between USB, parallel, serial sources

PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins	9 pins
Number of columns	136 columns

PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s
Barcodes	Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	4 plus one original

CONNECTIVITY

Interfaces	USB 2.0 Type A, Bidirectional parallel, RS-232
------------	--

PAPER / MEDIA HANDLING

Document Feed	Single sheet rear, Continuous paper rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes
Paper Thickness Continuous Paper	0.065 mm - 0.39 mm
Paper Thickness Multi Part	0.14 mm - 0.39 mm
Paper Thickness Single Sheet	0.065 mm - 0.14 mm

GENERAL

Energy Use	33 W, 1.1 W (standby)
Supply Voltage	AC 220 V - 240 V
Energy Star	Yes
Product dimensions	546 x 275 x 164 mm (Width x Depth x Height)
Product weight	6.6 kg
Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows 98, Windows Server 2008 R2, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	10,000 Hours
Print Head Life	400 Million Strokes/Wire
Sound Pressure	Operation: 53 dB (A)
Memory	128 kB included
Ribbon Yield	4000000 characters Black Draft

OTHER

Warranty	24 months Carry in Optional warranty extension available
----------	---

LOGISTICS INFORMATION

SKU	C11CD24301A0
EAN code	8715946540573
Dimensions Single Carton	377 x 640 x 222 mm
Carton Weight	7.72 Kg
Multiple Order Quantity	1 Units
Country of Origin	Indonesia
Pallet Size Euro	27 Units
Pallet Size Block	27 Units

Epson LX-1350

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

- SIDM Black Ribbon Cartridge for LX-1350, LX-1170II, LX-1170 (C13S015642) (C13S015642)

OPTIONAL ACCESSORIES

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series
C12C811141

For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON[®]