



Maximize the value of your video security.

Introducing the Sarix IL10 Series micro dome and mini IP cameras

The new Sarix™ IL10 series mini box and micro dome cameras are high-definition, cost-effective IP network cameras perfect for most any indoor fixed video security application. The IL10 Series cameras produce high-quality, color HD video, and the integrated prefocused fixed focal length lens makes sharp scene alignment and installation quick and easy. The box camera models offer unique mounting flexibility, and the micro dome models ship with quick snap-in ceiling mounts. Convenient network connectivity, Power over Ethernet (PoE) models, and a simple Web user interface make for easy plug-and-play finalization of settings and positioning adjustment. And by delivering industry-leading Sarix image quality, backed by the Pelco™ by Schneider Electric™ satisfaction guarantee, the IL10 Series are value-driven cameras that you can choose with confidence.



www.pelco.com

Choose with confidence.

PELCO
by Schneider Electric

Sarix IL10 Series micro dome and mini IP cameras features



The IL10 Series easily connects to Pelco IP and hybrid systems such as Endura™ version 2.0 (or later), Digital Sentry™ version 7.3 (or later), and DX4700/DX4800 hybrid video recorders. The IL10 Series is also compatible with Pelco API v1.0 and the ONVIF™ Profile S standard for connection with third-party video management systems.

Web interface

The IL10 Series uses a standard Web browser for easy remote setup and administration. Controls are optimized for easy one-step camera configuration for features including color, exposure, flicker control, and streaming. A one-click shutter allows you to capture sharp JPEG snapshots of the live view for documenting, positioning, or easy event recording.

Video streams

IL10 Series cameras can support two simultaneous video streams. The two streams can be compressed in H.264 format that can be individually optimized between highest quality and bandwidth/storage efficiency. The camera supports text overlay with options for time, date, and camera name.

Convenient power


IL10 Series PoE models work with PoE-enabled network switches or power injectors, eliminating the need for separate power supplies and cabling. The 24 Vac models are also offered for installations where 24 Vac power already exists. The IL10 Series comes in four options suitable for a variety of indoor environments:

- IL10-BP Sarix Indoor Box Camera - PoE
- IL10-BA Sarix Indoor Box Camera - 24Vac
- IL10-DP Sarix Indoor Micro Dome - PoE
- IL10-DA Sarix Indoor Micro Dome - 24Vac



PRODUCT AT A GLANCE

- 720p (1,280 x 720) resolution
- 30 images per second (ips)
- H.264 compression
- Up to two simultaneous video streams
- Selectable bit rate
- Minimum illumination down to 0.5 lux
- Integrated 68° field of view lens
- Web-based user interface for easy setup and configuration
- Power over Ethernet (IEEE 802.3af) or 24 Vac options
- Compatible with Pelco and third-party video systems
- ONVIF Profile S conformant
- One-year warranty and support from Pelco by Schneider Electric



Contact the manufacturer's representative in your area today, or visit www.pelco.com to download complete specification sheets.